

Swage Button S-409



General:

- Swage button terminations have an efficiency rating of 98% based on the catalog strength of wire rope.
- Special processed, low carbon steel.
- COLD TUFF for better swageability.
- Stamp for identification after swaging without concern for fractures (as per directions in the wire rope end terminations user's manual).



Select a row from the table below, then click the add to quote button

Part Code	Stock no.	Size no.	Rope size in	Rope size mm	Weight per 100 lbs	Before swage dimensions in A	Before swage dimensions in B	Before swage dimensions in C	After swage dimensions in D maximum after swage dimensions	After swage dimensions in E length	Die description	Stock no. 500 tons 1000 tons 1500 tons 5 x 7
--	1,040,171	1 SB	1/8	3	2	0.42	0.5	0.14	0.4	0.61	1/8 - 1/4 Button	1,191,621
--	1,040,215	3 SB	3/16	5	4	0.56	0.7	0.2	0.52	0.84	1/4 1st Stage	1,197,528
--	1,040,251	5 SB	1/4	6-7	8	0.68	1.06	0.31	0.58	1.41	1/8 - 1/4 Button	1,191,621
--	1,040,297	7 SB	5/16	8	16	0.88	1.13	0.36	0.77	1.33	3/8 1st Stage	1,192,364
--	1,040,313	8 SB	3/8	9-10	15	0.88	1.48	0.42	0.77	1.69	3/8 1st Stage	1,192,364
--	1,040,331	9 SB	7/16	11	30	1.13	1.63	0.48	1.03	1.94	1/2 1st Stage	1,192,408
04B0747	1,040,359	10 SB	1/2	13	50	1.31	1.89	0.55	1.16	2.17	5/8 Socket	1,192,907
--	1,040,377	11 SB	9/16	14	70	1.44	2.02	0.61	1.29	2.41	9/16 - 5/8 Button	1,191,665
04B0746	1,040,395	12 SB	5/8	16	100	1.56	2.42	0.67	1.42	2.89	3/4 Socket	1,192,925
--	1,040,411	13 SB	3/4	18-20	131	1.68	2.74	0.8	1.55	3.25	3/4 1st Socket	1,192,462
--	1,040,439	14 SB	7/8	22	220	2	3.27	0.94	1.8	3.86	7/8 1st Stage	1,192,480
04B0748	1,040,457	15 SB	1	25-26	310	2.25	3.67	1.06	2.05	4.36	1 1st Stage	1,192,505
--	1,040,475	16 SB	1-1/8	28-29	450	2.56	4.05	1.19	2.3	4.81	1-1/8 1st Stage	1,192,523
04B0749	1,040,493	17 SB	1-1/4	31-32	650	2.81	4.57	1.33	2.56	5.42	1-3/8 Socket	1,193,023

1

Add to quote

